



### 40ft 3-axle gooseneck skeleton semi trailer with Fuwa 13T axle

As the professional manufacturer, we would like to provide you high quality JUPITER® BRAND 40FT 3-AXLE GOOSENECK SKELETON SEMI TRAILER. And we will offer you the best after-sale service and timely delivery. JUPITER® is a large-scale semi trailer and special vehicles manufacturer and supplier in China. We have been specialized in semi trailer and special vehicles for more than 38 years. Our 40ft 3-axle gooseneck skeleton semi trailer with Fuwa 13T axle have a good price and quality advantage and had already exported to the Asia, Africa and South America countries. We look forward to becoming your long-term partner in China

#### Product Description

This JUPITER® 40ft 3-axle gooseneck skeleton semi trailer is suitable for carrying ISO 20FT and 40FT containers, which are mostly used in the port, pier and container yards. 40ft 3-axle gooseneck skeleton semi trailer with JOST 2 inch King Pin is the best choice for the transportation and operation of 20ft and 40ft container van box with high efficiency and economic return, we use famous brand parts on 40ft 3-axle gooseneck skeleton semitrailer with 6 locks, such as FUWA or BPW Brands Axle, JOST King Pin.so we recommend the end users or drivers to choose this 40ft 3-axle gooseneck skeleton semi trailer with Fuwa 13T axle and welcome to inquiry about our 40ft 3-axle gooseneck skeleton semi trailer.

## JUPITER® 40FT 3-AXLE GOOSENECK SKELETON SEMI TRAILER Parameter (Specification)

Specification:	
Type:	40FT3 Axles Gooseneck Skeleton Trailer
Model:	JPT9401TJZG
Dimension:	
Length:	12,420mm

Width:	2,480mm
Height:	1,560mm
Wheel Base:	7500+1310+1310mm
<b>Frame &amp; Structure:</b>	
Main beam:	Material Q345B. Fabricated "H" beam height 500mm, Top flange thickness 12mm, Middle web thickness 6mm, Bottom flange thickness 14mm
Side beam:	14# channel steel
Platform:	2.5mm thick diamond plate with supporting channel, 4 lines 40*30 shaped steel
Kingpin:	2'(50#), bolted in type
Twist lock:	6 sets twist locks
Welding standard:	All welding are to be done by qualified welder per applicable national standard
Painting:	Shot blast at Standard SA 2.5 prior to application of primer, polyurethane top coat. Total DFT not less than 100um
<b>Running gear:</b>	
Suspension:	mechanical suspension, heavy duty leaf spring 8pcs-16mmx90mm, China
Axle:	Factory standard 3 pcs*13 ton capacity, China
Brake system:	Dual line pneumatic brake, SAE hose and connector, without ABS
Brake chamber:	4 units T30/30 spring brake chambers, 2 units T30 brake chambers
Air tank:	40L, 1pc, China
Tire:	11R22.5, 12 pcs. China
Rim:	8.25*22.5 steel disc wheel, 10 holes ISO, 12 pcs. China
Landing gear:	Fuwa 28T two speed telescopic manual landing gear
<b>Electrical System:</b>	
Voltage:	24 Volt

Receptacle:	7 way socket SAE standard, China
Front marker lamp:	White
Side marker lamp:	White & Red
Rear lamp:	Red
Turn signal lamp:	Amber
Reflector:	Per customer requirement
Wiring:	Electric cable protected by PVC conduit on main frame
<b>Accessories:</b>	
Mud guard:	Steel mud guard
Spare wheel carriers:	1 pc
Tool box:	1 pc
Note: All the details not mentioned above should comply with Chinese regulations.If any component or structure changed, the price shall be modified accordingly.	